## **Federal Communications Commission**

- (a) The nature of such extinguishment or improper functioning.
- (b) The date and time the extinguishment or improper operation was observed or otherwise noted.
- (c) Date and time of FAA notification, if applicable.
- (d) The date, time and nature of adjustments, repairs, or replacements made.

 $[48\ FR\ 38477,\ Aug.\ 24,\ 1983,\ as\ amended\ at\ 61\ FR\ 4364,\ Feb.\ 6,\ 1996]$ 

### §17.50 Cleaning and repainting.

Antenna structures requiring painting under this part shall be cleaned or repainted as often as necessary to maintain good visibility.

[61 FR 4364, Feb. 6, 1996]

# § 17.51 Time when lights should be exhibited.

- (a) All red obstruction lighting shall be exhibited from sunset to sunrise unless otherwise specified.
- (b) All high intensity and medium intensity obstruction lighting shall be exhibited continuously unless otherwise specified.

[40 FR 30267, July 18, 1975, as amended at 61 FR 4364, Feb. 6, 1996]

## $\S 17.53$ Lighting equipment and paint.

The lighting equipment, color or filters, and shade of paint referred to in the specifications are further defined in the following government and/or Army-Navy aeronautical specifications, bulletins, and drawings (lamps are referred to by standard numbers):

TT-P-1021 (Color No. 17875 FS-595).
TT-P-59 <sup>1</sup> (Color No. 12197, FS-595).
TT-E-489 <sup>1</sup> (Color No. 12197 FS-595).
MIL-C-25050 <sup>2</sup> .
CAA-446 <sup>3</sup> Code Beacons, 300 mm.
MIL-62732.
L-810 <sup>3</sup> (FAA AC No. 150/ 5345-2 <sup>4</sup> ).
MIL-L-7830 <sup>2</sup> .
FAA/DOD L-856 (FAA AC No. 150/5345-43B4).
No. 116 A21/TS (6,000 h).
No. 125 A21/TS (6,000 h).
No. 620 PS-40 (3,000 h).

700-Watt lamp	No. 700 PS-40 (6,000 h).
<sup>1</sup> Copies of this specificatio Specification Activity, Building ons Plant, 1st and N Streets, S	n can be obtained from the 197, Room 301, Naval Weap-E., Washington, D.C. 20407.

<sup>2</sup> Copies of Military specifications can be obtained by contacting the Commanding Officer, Naval Publications and Forms Center, 5801 Tabor Ave., Attention: NPPC-105, Philadelphia, Pa. 19120.

Forms Center, 5801 Tabor Ave., Attention: NPPC-105, Philadelphia, Pa. 19120.

<sup>3</sup> Copies of Federal Aviation Administration specifications may be obtained from the Chief, Configuration Control Branch, AAF-110, Department of Transportation, Federal Aviation Administration, 800 Independence Avenue SW., Washington, D.C. 20591.

vvasimigiun, D.C. 20591.

<sup>4</sup> Copies of Federal Aviation Administration advisory circulars may be obtained from the Department of Transportation, Publications Section, TAD-443.1, 400 7th St. SW., Washington, D.C. 20590.

[33 FR 11540, Aug. 14, 1968, as amended at 40 FR 30267, July 18, 1975]

#### §17.54 Rated lamp voltage.

To insure the necessary lumen output by obstruction lights, the rated voltage of incandescent lamps used shall correspond to be within 3 percent higher than the voltage across the lamp socket during the normal hours of operation.

[42 FR 54826, Oct. 11, 1977]

# § 17.56 Maintenance of lighting equipment.

- (a) Replacing or repairing of lights, automatic indicators or automatic control or alarm systems shall be accomplished as soon as practicable.
- (b) The flash tubes in a high intensity obstruction lighting system shall be replaced whenever the peak effective daytime intensity falls below 200,000 candelas.

[40 FR 30267, July 18, 1975]

# § 17.57 Report of radio transmitting antenna construction, alteration, and/or removal.

The owner of an antenna structure for which an Antenna Structure Registration Number has been obtained must notify the Commission within 24 hours of completion of construction (FCC Form 854–R) and/or dismantlement (FCC Form 854). The owner must also immediately notify the Commission using FCC Form 854 upon any change in structure height or change in ownership information.

[61 FR 4364, Feb. 6, 1996]